


Nominal Size mm/in	Pipe O.D mm/in	Dimensions			Bolt/Nut	Working pressure (Psi)
		D	L	n-Φ	No.-size (mm)	
		mm	mm			
50	60.3	164	210	4-18	3/8×2-1/8 (M10×55)	250
2	2.375			4-18		
65	73	176	240	4-18	3/8×2-3/4 (M10×70)	
2½	2.875			4-18		
80	88.9	192	250	4-18		
3	3.5			4-18		
100	114.3	224	278	8-18		
4	4.5			8-18		
125	141.3	254	310	8-22		
5	5.563			8-22		
150	168.3	282	336	8-22	1/2×3-1/8 (M12×80)	
6	6.625			8-22		
200	219.1	343	395	8-22		
8	8.625			8-22		
250	273	362	503	12-26	1/2×4 (M16×100)	
10	10.75			12-26		
300	323.9	432	580	12-26		
12	12.75			12-26		

Grooved Flange ANSI125/150
L991

Nominal Size mm/in	Pipe O.D mm/in	Dimensions				Working pressure (Psi)
		ΦD mm	Φd mm	H mm	n-Φ mm	
50	60.30	165	125	60	4-18	300
2	2.38				4-18	
65	73.00	185	145	60	4-18	
2 1/2	2.88				4-18	
65	76.10	185	145	60	4-18	
2 1/2	3.00				4-18	
80	88.90	200	160	60	8-18	
3	3.50				8-18	
100	108.00	220	180	60	8-18	
4	4.25				8-18	
100	114.30	220	180	60	8-18	
4	4.50				8-18	
125	133.00	250	210	65	8-18	
5	5.25				8-18	
125	139.70	250	210	65	8-18	
5	5.50				8-18	
125	141.30	250	210	65	8-18	
5	5.56				8-18	
150	159.00	285	240	65	8-22	
6	6.25				8-22	
150	165.10	285	240	65	8-22	
6	6.50				8-22	
150	168.30	285	240	65	8-22	
6	6.63				8-22	
200	219.10	340	295	70	12-22	
8	8.63				12-22	
250	273.00	405	355	72	12-26	
10	10.75				12-26	
300	323.90	460	410	72	12-26	
12	12.75				12-26	

Flange Adaptor PN16
XGQT08