



- 200 PSI WOG
- 150 PSI WSP
- Cuerpo de bronce
- Tapa roscada
- Cara de P.T.F.E. en disco para sello positivo
- Instalación vertical u horizontal
- Extremos roscados cumplen ANSI B1.20.1
- Extremos soldables cumplen ANSI B16.18

CHECK CUMPIO BRONCE 200 WOG BRONCE

	CÓDIGO	DIÁMETRO	INNER/MASTER CANTIDAD	PESO/CAJA (LBS.)	PESO/CAJA (KG)
ROSCABLE	101-203	1/2"	10/120	73.0	33.1
	101-204	3/4"	10/80	79.0	35.8
	101-205	1"	10/60	78.0	35.4
	101-206	1-1/4"	5/30	59.0	26.8
	101-207	1-1/2"	4/24	71.0	32.2
	101-208	2"	2/16	78.0	35.4
SOLDABLE	101-703	1/2"	10/120	70.0	31.8
	101-704	3/4"	10/80	74.0	33.6
	101-705	1"	10/60	67.0	30.4
	101-706	1-1/4"	5/30	61.0	27.7
	101-707	1-1/2"	4/24	66.0	29.9
	101-708	2"	2/16	50.0	22.7



- 200 PSI WOG
- Cumple estándar NSF de bajo plomo
- Extremos roscados cumplen ANSI B1.20.1
- Extremos lisos cumplen ANSI B16.18

CHECK HORIZONTAL 200 WOG BRONCE

	CÓDIGO	DIÁMETRO	INNER/MASTER CANTIDAD	PESO/CAJA (LBS.)	PESO/CAJA (KG)
ROSCABLE	101-003	1/2"	10/100	42.0	19.1
	101-004	3/4"	5/60	33.0	15.0
	101-005	1"	5/40	29.0	13.2
	101-006	1-1/4"	5/30	42.0	19.1
	101-007	1-1/2"	4/24	40.0	18.1
	101-008	2"	2/16	45.0	20.4
	101-009	2-1/2"	2/8	42.0	19.1
	101-010	3"	1/6	44.0	20.0
	101-011	4"	1/3	38.0	17.2
SOLDABLE	101-503	1/2"	10/100	40.0	18.1
	101-504	3/4"	5/60	33.0	15.0
	101-505	1"	5/40	32.0	14.5
	101-506	1-1/4"	5/30	43.0	19.5
	101-507	1-1/2"	4/24	41.0	18.6
	101-508	2"	2/16	45.0	20.4